





NOTES:

1.MATERIAL:

MOLDING: LCP UL94 V-0
CONTACT: COPPER ALLOY.
GOLD PLATED Min ON CONTACT AREA, 100u"
Min TIN (LEAD FREE) ON SOLDER AREA,
SHELL: SUS201-H, T=0.30±0.03mm
50u" NICKEL PLATING OVER ALL.

2.MECHANICAL:

INSERTION: 5~20N.
EXTRACTION: 8~20N AFTER TEST.
DURABILITY: 5000 CYCLES

3.ELECTRICAL:

CURRENT: 3A FOR VBUS;
1.25A FOR GND PIN.
0.25A FOR OTHER.

VOLTAGE: 20 V MAX
WITHSTANDING VOLTAGE: 100V AC R.M.S.
CONTACT RESISTANCE: 40mΩ MAX.
INSULATION RESISTANCE: 100MΩ MIN.

4.ENVIRONMENTAL

TEMPERATURE RANGE -25°C ~ +85°C

5. 尺寸标注事项:

图示有标示⊗者为首样全检, 重点管控尺寸.

6. 产品符合RoHS标准.

CMTDDZ 东莞市田都科技有限公司
Dongguan TianDu Technology Co. Ltd.

.X: ±0.35	.X': ±1.5'	INTENDED USE: CONNECTOR	TITLE: TYPE-C 2P 直插9.3母座	
.XX: ±0.25	.XX': ±1.0'		PART NO.:	SEE TABLE
.XXX: ±0.20	.XXX': ±0.5'	APPD.:	DWG. NO.:	T11-02LC01-9.3H
MAT'L.:		CHKD.:	SCALE:	1:1
SEE NOTES		DR.:	UNIT:	mm
FINISH:			REV.:	A0