

CMTDDZ

规格说明: Specifications:

电气特性: Electrical:

- 额定电流: Current Rating
1.5A/contact terminal
- 额定电压: Voltage Rating
30V DC
- 接触阻抗: Contact Resistance
30 milliohms MAX
- 耐电压: Dielectric Withstanding Voitage:
500 V AC AT Sea Level
- 绝缘阻抗: Insulation Resistance:
1000MEGA ohms MIN

物理性能: Mechanical:

- 插拔力: Cnnector Mate and Unmate Force
Mate force: 3.57kgf(MAX)
Unmate force: 1.02kgf(MIN)
- 端子保持力: Terminal Retention
1.0kgf(MIN)

原材料: Material:

- 塑胶: Housing:
Hing Temperature Thermaplastics,
- 端子: Contact: Copper Alloy C2680
- 外壳: Shell: Copper Alloy C2680/SPCC

电镀: Finish:

- 端子: Contact: Plated Gold in Mating Area,
Tin On Solder Talls
端子四周镀50U"(MIN)锡, 镀金区域镀100-200U"镀金1U"
- 外壳: Shell:
铜壳四周镀80U"(MIN)锡

Nickel Plating

成品图 MANUFACTURE DWG		公差一览表 TOLERANCE UNLESS OTHERWISE		日期 DATE		单位 UNIT		制图 DRAWING		DWG NO.	
.X±0.15	X.±5°	.X±0.15	X.±2°	2016.10.20	MM	比例 SCALE	1 : 1	设计 DESIGN	ERIC	品名 NAME	T10-2F680GS
.XX±0.05	.XX±2'	.XX±0.05	.XX±1'	审核 CHECKED	角法 VIEW			版本 VER	A0	页数 SHEET	004
.XXX±0.02	.XXX±1'			核准 APPROVE							

**CMTDDZ 东莞市田都科技有限公司
Dongguan TianDu Technology Co., Ltd.**

短体6.8直边全贴

成 品 圖 MANUFACTURE DWG 公 差 一 覽 表 TOLERANCE UNLESS OTHERWISE		CMTDDZ 东莞市天都科技有限公司 Dongguan TianDu Technology Co. Ltd.									
X±0.15	X±5°	日 期 DATE	2016.10.20	單 位 UNIT	MM	創 圖 DRAWING		DWG NO.	T10-2F680GS		
XX±0.05	.X±2°	审 核 CHECKED		比 例 SCALE	1 : 1	设 计 DESIGN	ERIC	品 名 NAME	箱体6.8直边全贴		
XXX±0.02	.XX±1°	核准 APPROVE		角 注 VFW				版 本 VFR	AO	頁 數 SHEET	004